

H. D. SHELDON & COMPANY, INC.

143 WEST 29TH STREET, NEW YORK, NY 10001

TEL. (212) 924-6920 • FAX (212) 627-1759

E-MAIL: SALES@HDSHELDON.COM

HOT ADDENDUM TO HATCO EXPORT PRICE LIST

May 1, 2015

Toast-Max® Conveyor Toaster

Flexibility and performance are yours with the economical Toast-Max Conveyor Toasters. Using conveyor speed, not temperature, to determine toasting color, allows for instant adjustment of

toasting time. Toast-Max features an easy-to-use 4-position toast selector switch with off / toast / buns / stand-by (power save mode).

CONVEYOR TOASTER

Model	Description	List Price	Cap./Min.†	Dimensions (W x D x H*) w/Legs	Voltage	kW	Ship Weight
TM-5H	Bread & Buns	\$859.	3 slices	289 x 416 x 387 mm (11 1/2" x 16 3/8" x 15 1/4")	220-240	1.3-1.6	16 kg (36 lbs.)
TM-10H	Bread & Buns	999.	6 slices	368 x 416 x 387 mm (14 1/2" x 16 3/8" x 15 1/4")	220-240	1.9-2.3	19 kg (41 lbs.)

† Toasting capacity may vary by product. Toasting of coated products not recommended.
* Height includes 102 mm (4") legs.

All Conveyor Toasters Models Feature:

Voltage:220-240V, 50/60 Hz, single phase.
Maximum Product Size – TM-5H:187 W x 64 H mm (7 3/8" x 2 1/2").
– TM-10H:264 W x 64 H mm (10 3/8" x 2 1/2").
Cord Location:1829 mm (6") – Left side of back of unit near bottom.
ALL TOAST-MAX METAL SHEATHED HEATING ELEMENTS WARRANTED AGAINST BURNOUT AND BREAKAGE FOR ONE YEAR.



Push-up Toasters

Perfect for self-serve areas and lighter volume applications, the Hatco Push-Up Toasters provide even golden toasting of a variety of bread products. The durable stainless steel

housing contains four self-centering extra wide slots with individual toasting controls and removable crumb tray.

PUSH-UP TOASTER

Model	Description	List Price	Dimensions (W x D x H)	KW	Ship Weight
TPT-230-4	Four Slice Push-up	\$415.	346x 313 x 204mm (14 3/4" x 12 15/16" x 9 1/4")	2.5	10 kg (22 lbs.)

† Toasting capacity may vary by product. Toasting of coated products not recommended.

All Push-Up Toasters Feature:

Voltage:230V, single phase.
Slot Openings – TPT-230-4:32 W x 140 D mm (1 1/4" x 5 1/4").
Bread Types:All.
Maximum Product Thickness:22 mm (7/8").
Cord Location:1829 mm (6") on bottom, back right.
Toasting capacity may vary by product. Toasting of coated products not recommended.
ONE YEAR REPAIR OR REPLACE WARRANTY, CONTACT HATCO SERVICE FOR DETAILS.



TPT-230-4



Heat-Max Heated Wells

The multipurpose Heated Well from Hatco offers the flexibility of food warmers, soup kettles, bain-marie heaters, steamers, and pasta cookers all in one! With a range of temperature

settings, Heat-Max can boil pasta and soup noodles, steam dim sum, and warm and hold soups, curry, gravies, and toppings at safe serving temperatures.

FREESTANDING ROUND HEATED WELL

Model*	Description	List Price	Dimensions (W x D x H)	Watts	Ship Weight
--------	-------------	------------	------------------------	-------	-------------



RHW-1 with standard pot and lid

RHW-1	Round Single Well	\$603.	359 x 330 x 343 mm (14 ¹ / ₈ " x 13" x 13 ¹ / ₂ ")	1300	10 kg (22 lbs.)
RHW-2	Round Dual Well	998.	630 x 330 x 343 mm (24 ³ / ₄ " x 13" x 13 ¹ / ₂ ")	2500	17 kg (38 lbs.)

* Model number indicates number of wells, i.e., -2 (two wells).

All Freestanding Round Models Feature:

Voltage:230V, single phase.

Liquid Capacity – RHW-1:10 liters (11 qt.)

– RHW-2:2 x 10 liters (22 qt.)

RHW-1 Shipped with:One food holding pot and one pot lid.

RHW-2 Shipped with:Two food holding pots and two pot lids.

Cord Location:1830 mm (6') cord and plug, back of unit.

ALL HEAT-MAX HEATED WELLS WARRANTED FOR ONE YEAR PARTS.



RHW-2 with standard pots and lids (not shown)

BUILT-IN ROUND HEATED WELL

Model	Description	List Price	Dimensions (W x D x H)	Watts	Ship Weight
-------	-------------	------------	------------------------	-------	-------------



RHW-1B with standard pot, lid, and remote control, ladle not included

RHW-1B	Round Single Well Built-in	\$603.	360 x 330 x 330 mm (14 ¹ / ₈ " x 13" x 13")	1300	10 kg (21 lbs.)
--------	----------------------------	--------	---	------	-----------------

All Built-In Round Models Feature:

Voltage:230V, single phase.

Liquid Capacity:10 liters (11 qt.)

RHW-1B Shipped with:One food holding pan, one pan lid, and remote control.

Cord Location:1420 mm (56") cable from well to control box with a 1829 mm (6') cord and plug located at the back of the control box.

Recommended Well Cut-Out Size:300 mm (11¹³/₁₆") diameter.

ALL HEAT-MAX HEATED WELLS WARRANTED FOR ONE YEAR PARTS.


ACCESSORIES (PRICING APPLIES ONLY AT TIME OF EQUIPMENT PURCHASE) –

RHW-11QT-POTRHW 10.4 liter (11 qt.) Pot\$104.

RHW-11QT-LIDRHW Lid for 10.4 liter (11 qt.) Pot61.



RHW-11QT-POT
10-Liter Round Pot



RHW-11QT-LID
Lid for 10-Liter
Round Pot



FREESTANDING & BUILT-IN RECTANGULAR HEATED WELL

Model	Description	List Price	Dimensions (W x D x H)	Watts	Ship Weight
-------	-------------	------------	------------------------	-------	-------------



Model RCTHW-1

RCTHW-1	Rectangular Heated Well*	\$626.	368 x 611 x 282 mm (14 ¹ / ₂ " x 24" x 11 ¹ / ₈ "	3000	12 kg (26 lbs.)
RCTHW-1B	Rectangular Heated Well Built-in♦	593.	368 x 582 x 226 mm (14 ¹ / ₂ " x 22 ¹⁵ / ₁₆ " x 8 ⁷ / ₈ "	3000	13 kg (29 lbs.)

* Model includes control on end panel. ♦ Model includes remote control.

All Rectangular Models Feature:

Voltage:230V, single phase.
 Cord Location – RCTHW-1: 1829 mm (6') cord and plug, back of unit.
 – RCTHW-1B: 1420 mm (56") cable from well to control box with a 1830 mm (6') cord and plug located at the back of the control box.
 RCTHW-1 Shipped with:Built-in drain valve and 600 mm (23⁵/₈" drain hose.
 RCTHW-1B Shipped with:600 mm (23⁵/₈" drain hose w/valve, Remote control.
 Recommended Well Cut-Out Size:550 mm W x 344 mm D (21⁵/₈"x13⁹/₁₆").
ALL HEAT-MAX HEATED WELLS WARRANTED FOR ONE YEAR PARTS.



Model RCTHW-1B

FREESTANDING & BUILT-IN PASTA COOKER

Model	Description	List Price	Dimensions (W x D x H)	Watts	Ship Weight
-------	-------------	------------	------------------------	-------	-------------



Model RCTHW-6

RCTHW-6	Pasta Cooker Free-standing*	\$1071.	368 x 610 x 282 mm (14 ¹ / ₂ " x 24" x 11 ¹ / ₈ "	6000	15 kg (33 lbs.)
RCTHW-6B	Pasta Cooker Built-in♦	1116.	390 x 610 x 286 mm (15 ³ / ₈ " x 24" x 11 ¹ / ₄ "	6000	17 kg (37 lbs.)

* Model includes control on end panel. ♦ Model includes remote control.

All Paster Cooker Models Feature:


Voltage – Single Phase:230V.
 – Three Phase:230/400V.
 RCTHW-6 Shipped with: Auto-fill, Built-in drain valve.
 RCTHW-6B Shipped with: Auto-fill, remote control and 1420 mm (56") cable fromwell to control box.
 Power Location– RCTHW-6: Back of unit, no cord supplied.
 – RCTHW-6B: Located on bottom of well, no cord supplied.
 Recommended Well Cut-Out Size: 570 mm W x 344 mm D (22⁷/₁₆"x13⁹/₁₆").
ALL HEAT-MAX PASTA COOKERS WARRANTED FOR ONE YEAR PARTS.




Model RCTHW-6B

ACCESSORIES (PRICING APPLIES ONLY AT TIME OF EQUIPMENT PURCHASE) –


RCTHW-SK	RCTHW Soup Kettle Plate (7 liter (7 qt.) pot not included).....	\$153.
RCTHW-SW	RCTHW Bain-Marie/Sauce Warmer Plate (4 liter (4 qt.) pot not included).....	158.
RCTHW-SP	RCTHW Steamer Plate (6-Holes).....	126.
RCTHW-PC	RCTHW Pasta Cooker Plate (Standard for RCTHW-6/-6B).....	221.
RCTHW-BASKET	RCTHW Noodle Basket with Stainless Steel Handle.....	25.
4QT-PAN	4-Liter (4 QT) Round Pan.....	75.
7QT-PAN	7-Liter (7 QT) Round Pan.....	85.
4QT-LID-1	4-Liter (4 QT) Notched Lid.....	36.
7QT-LID-1	7-Liter (7 QT) Notched Lid.....	46.




RCTHW-SK
 Soup Kettle Plate
 (accommodates two
 7-liter (7 qt.) pots with
 lids)



RCTHW-SW
 Bain-Marie/Sauce
 Warmer Plate
 (accommodates three,
 4-liter (4 qt.)pots with
 lids)




RCTHW-SP
 Steamer Plate (6-Holes)




RCTHW-PC
 Pasta Cooker Plate
 (accommodates six
 RCTHW baskets)




RCTHW-BASKET
 Noodle Basket with
 Stainless Steel Handle




4QT-PAN
 4 Liter (4 QT)
 Round Pan



7QT-PAN
 7 Liter (7 QT)
 Round Pan



4QT-LID-1
 4 Liter (4 QT)
 Notched Lid



7QT-LID-1
 7 Liter (7 QT)
 Notched Lid



Drawer-Max™ Drawer Warmer

Hold everything from meat to vegetables to rolls in a Hatco Freestanding or Built-in Drawer-Max Drawer Warmer. Each drawer features adjustable sliding vents and individual

thermostatic controls to hold a variety of hot food safely for peak serving periods and are built to withstand tough kitchen environments.

DRAWER WARMER

Model	Description	List Price	Dimensions (W x D x H)	Ship Weight
HDM-2	Freestanding Two Drawer Warmer	\$1803.	749 x 576 x 614 mm (29 1/2" x 22 1/16" x 24 3/16")	74 kg (163 lbs.)
HDM-2B	Built-in Two Drawer Warmer	1765.	743 x 568 x 512 mm (29 1/4" x 22 3/8" x 20 3/16")	70 kg (154 lbs.)



HDM-2

All Drawer Warmers Feature:

Voltage:230V, single phase, 984 watts, 4.3 amps, CEE 7/7 Schuko, BS-1363, and AS 3112 Plug.
 Model Shipped with – HDM-2:Black powdercoated cabinet, one 152 mm (6") deep food pan per drawer, 102 mm (4") plastic legs, 1829 mm (6') cord and plug.
 – HDM-2B:One 152 mm (6") deep food pan per drawer, 1829 mm (6') cord and plug.

Cord Location:Back of unit, lower left corner.

ALL DRAWER WARMER HEATING ELEMENTS ARE WARRANTED AGAINST BURNOUT OR BREAKAGE FOR ONE YEAR.

ALL DRAWER SLIDES AND ROLLERS ARE WARRANTED AGAINST BREAKAGE FOR ONE YEAR.

Flav-R-Fresh® Impulse Display Cabinets

A profitable way to create impulse food sales is with the small Flav-R-Fresh Holding and Display Cabinet. Using controlled moisturized heat allows you to showcase

your product longer using minimum counter space. Models available with rotating and stationary racks.

IMPULSE CABINET

Model ¹	Description ²	List Price ³	Dimensions (W x D x H) ⁴	Ship Weight
FDWDE-1	1 Door w/Circle Rack	\$2495.	492 x 530 x 727 mm (19 3/8" x 20 7/8" x 28 5/8")	38 kg (84 lbs.)
FDWDE-1X	1 Door w/Multi-Purpose Rack	2404.	492 x 530 x 727 mm (19 3/8" x 20 7/8" x 28 5/8")	38 kg (84 lbs.)
FDWDE-2	2 Doors w/Circle Rack	2619.	492 x 559 x 727 mm (19 3/8" x 22" x 28 5/8")	38 kg (84 lbs.)
FDWDE-2X	2 Doors w/Multi-Purpose Rack	2527.	492 x 559 x 727 mm (19 3/8" x 22" x 28 5/8")	38 kg (84 lbs.)

¹ Models FDWDE-1 and FDWDE-2 include rack motor. Models with "X" designator do not have revolving display and are NOT available for retrofit.

² Rack listed is included with unit. Other racks available – deduct price of included rack and add price of substituted rack to list price.

³ For non-humidified cabinet, deduct \$210. Unit will only operate in dry mode.

⁴ Height includes standard 25 mm (1") legs.

All Impulse Cabinets Feature:

Voltage:220V, 50Hz, 1440 watts, 6.7 amps, CEE 7/7 Schuko and BS-1363 Plug.

Cabinet Opening:400 W x 502 H mm (15 3/4" x 19 3/4").

Door Hinges – Control Side:Left-hand side.

– Customer Side (Two-door models only):Right-hand side.

Max. Pizza Size:381 mm (15") diameter.

Water Tank Capacity for Humidity System:2 liters (1/2 gallon).

Cord Location:1829 mm (6') cord and plug, Facing controls, left-hand side panel, lower right corner.

ALL FLAV-R-FRESH METAL SHEATHED AIR HEATING ELEMENTS WARRANTED AGAINST BURNOUT AND BREAKAGE FOR ONE YEAR.



FDWDE-1 with rotating 4-tier circle rack

OPTIONS (NOT FOR RETROFIT) –

Designer Colors – Non-standard colors are non-returnable –

RED Warm Red	\$328.	BLACK Black	\$328.	GRAY Gray Granite	\$328.
WHITE White Granite	328.	NAVY Navy Blue	328.	GREEN Hunter Green	328.
COPPER Antique Copper	328.				

FDWD-SCD Self closing door in lieu of standard door (Left hinge only) Must specify front, control, or both sides on FDWD-2 models, not field reversible **per door \$62.**

FDWD-6FRT 152 mm (6"), Merchandising Display Sign Holder for Control Side only (Includes metal holder only). Available in all Designer colors to match your unit (Black is standard). Adds 29 mm (1 1/8") to height (height) of unit. Requires (1) sign 484 W x 83 H x 2 D mm (19 5/16" x 3 3/16" x 1/16") – not included **81.**

FDWD-6SIGN 162 mm (6 3/8"), One Sided Merchandising Display Sign Holder (Includes metal holder and window) – **one per side**, three maximum. Available in all Designer colors to match your unit (Black is standard). Adds 32 mm (1 1/4") to height of unit. Requires (1) sign 491 W x 159 H x 2 D mm (19 5/16" x 6 1/4" x 1/16") – not included **63.**

FDWD-DIS 76 mm (3"), One Sided Merchandising Display Sign Holder (Includes metal holder and window) – **one per side**, three maximum. Available in all Designer colors to match your unit (Black is standard). Adds 32 mm (1 1/4") to height of unit. Requires (1) sign 484 W x 83 H x 2 D mm (19 1/16" x 3 1/4" x 1/16") – not included **\$ 57.**

ACCESSORIES –

FDWD-LEGS 102 mm (4") Adjustable Legs 102-127 mm (4"-5") **\$ 60.**

COUPLING Motorless Rack Coupling for FDWD-1X and -2X Models (Select Circle Rack or Pretzel Tree) **33.**

FDWD4TCR 4-Tier Circle Rack with Pizza Pan Retainers (Requires Coupling for -1X or -2X models) **181.**

FDWD4SMP 4-Shelf Multi-Purpose Rack (Each shelf 346 W x 321 D mm (13 5/8" x 12 5/8")) **206.**

FDWD3TPT 3-Tier Pretzel Tree (Requires Coupling for -1X or -2X models) **206.**

Graphic Adhesive Decals (3 per set) 423 W x 140 H mm (16 5/8" x 5 1/2") –

FDWD-PIZZA Three Pizza Photo Decals **\$115.**

HOT PIZZA Three "Hot Pizza" Decals **44.**

HOT PRETZEL Three "Hot Pretzels" Decals **44.**



H.D. Sheldon HOT Addendum
 Telephone: (414) 671-6350 • Fax: (414) 671-3976 • www.hatcocorp.com • May 1, 2015

Glo-Ray® Portable Foodwarmer

Opt for the versatility of Hatco's Glo-Ray® Portable Foodwarmers. These foodwarmers offer design flexibility without sacrificing food product quality. Ideal for use next to fry stations,

drive-through windows, and service areas that require frequent and easy access.

PORTABLE FOODWARMER WITH METAL SHEATHED ELEMENTS

Model	Description	List Price	Dimensions (W x D x H)	Watts	Ship Weight
GMFFL	Portable Foodwarmer	\$340.	329 x 644 x 445 mm (13" x 25 ³ / ₈ " x 17 ¹ / ₂ "	610	8 kg (18 lbs.)

All GMFFL Models Feature:

Voltage:120V, 230V, single phase.

Model Shipped with:1829 mm (72") cord and plug, sign holder, and clear plastic insert for sign holder.

Cord Location:Back, upper middle.

ALL GLO-RAY METAL SHEATHED HEATING ELEMENTS WARRANTED AGAINST BURNOUT AND BREAKAGE FOR ONE YEAR.

OPTIONS (NOT FOR RETROFIT) –

Designer Colors, No Additional Charge –Non-standard colors are non-returnable –

REDWarm Red BLACK.....Black (Standard)



GMFFL
Black standard,
food pan not included

Quick-Therm Salamander

A notch above a traditional salamander, the Hatco Quick-Therm Salamander incorporates many unique features like plate activation, which serve to simplify operations and improve functional-

ity. With the Hatco Quick-Therm Salamander, you can now start cooking, grilling, reheating, or holding foods hot in just eight seconds!

SALAMANDER

Model	Description	List Price	Dimensions (W x D x H)	Watts	Ship Weight
QTS-1	Salamander	\$5056.	570 x 533 x 518 mm (22 ¹ / ₂ " x 21" x 20 ³ / ₈ "	4500	75 kg (166 lbs.)



QTS-1

All Salamander Models Feature:

Voltage:240/415V, 3 phase, 50/60 Hz, 6.5 Amps or .
230V, single phase, 50/60 Hz, 19.6 Amps.

Models Shipped with:Cooking grate and drip pan.

Cooking Area:546 W x 360 D x 70-185 H mm (21¹/₂" x 14¹/₄" x 2³/₄"-7¹/₄").

Power Location:Right side of back of unit near bottom (cord not included).

ALL QUICK-THERM SALAMANDER UNITS WARRANTED FOR ONE YEAR PARTS.

Therm-Max Salamander

Hatco's Therm-Max Salamander is specially designed for versatility in the kitchen with the capabilities to cook, grill, and reheat food. The unparalleled start up speed is a result

of "instant on" heating elements located in the upper housing of the salamander. Therm-Max Salamander is energy efficient and easy to operate.

SALAMANDER

Model	Description	List Price	Dimensions (W x D x H)	Watts	Ship Weight
TMS-1	Salamander	\$2645.	600 x 511 x 517 mm (23 ⁵ / ₈ " x 19 ⁷ / ₈ " x 20 ³ / ₈ "	4000	70 kg (155 lbs.)
TMS-1H	Salamander with Hold option	2645.	600 x 511 x 517 mm (23 ⁵ / ₈ " x 19 ⁷ / ₈ " x 20 ³ / ₈ "	4000	70 kg (155 lbs.)



TMS-1H

All Therm-Max Salamander Models Feature:

Voltage: TMS-1230V (single phase) or 230/400V (three phase), 50/60 Hz.

TMS-1H230V, single phase, 50/60 Hz.

Cooking Area:540 W x 373 D x 90-260 H mm (21¹/₄" x 14⁵/₈" x 3¹/₂"-10¹/₄").

Models Shipped With:Grill, drip pan, and wall mounting bracket.

Power Location:Right side of back of unit near bottom
(Cord without cap on TMS-1H model only).

ALL THERM-MAX SALAMANDER UNITS WARRANTED FOR ONE YEAR PARTS.



H.D. Sheldon HOT Addendum
Telephone: (414) 671-6350 • Fax: (414) 671-3976 • www.hatcocorp.com • May 1, 2015

Flow Max® Hot Water Dispenser

At the simple push of a button, the Hatco Flow Max Water Dispenser delivers pre-measured quantities of hot water for food and beverage preparation. Conveniently and safely provided hot water on demand for beverages, sauces, soups, gravy, cereals, rice, pasta,

potatoes, gelatins, and other applications. From single serve to high volume foodservice operations.

HOT WATER DISPENSER

Model	Description	List Price	Dimensions (W x D x H)	Ship Weight
FM2SS-7	Hot Water Dispenser Under-Counter	\$351.	256 x 305 x 454 mm (10 ¹ / ₈ " x 12" x 17 ⁷ / ₈ ")	7 kg (16 lbs.)
FM-5	Water Dispenser	2025.	342x347x391 mm (13 ¹ / ₂ " x 13 ¹¹ / ₁₆ " x 15 ⁷ / ₁₆ ")	18kg (40 lbs.)



FM2SS-7



FM-5

All Hot Water Dispensers Feature:

Voltage: FM2SS-7.....230V, single phase, 50/60 Hz, 2600 watts, 11.3 amps, and BS-1363.
 FM-5.....230V, single phase, 50/60 Hz, 1800 watts, 7.8 amps, and BS-1363, AS3112, CEE7/7 Schuko
 Capacity:7 liters (7 qt.).
 Cord Location:1829 mm (6') cord and plug, Back of unit, lower center.
ALL FLOW MAX WATER DISPENSERS WARRANTED FOR ONE YEAR PARTS.

Portable Warmers

The Hatco Heated Black Glass Shelves have a black tempered glass top surface to create uniform heat across the entire surface. The new design uses a modular system, whereby multiple

units can be placed side-by-side, with each unit's glass surface the size of a 1/1 GN food pan.

MODULAR BLACK GLASS

Model	Description	List Price	Dimensions (W x D x H)	Watts	Ship Weight
HGSM-4060	Heated Glass Shelf Modular	\$495.	400 x 600 x 56 mm(15 ³ / ₄ " x 23 ⁵ / ₈ " x 2 ¹ / ₄ ")	275-327	7.5 kg (17 lbs.)



HGSM-4060

All HGSM Models Feature:

Voltage:220-240V, single phase.
 Cord Location :1829 mm (6') cord and plug, Left back of unit.
ALL HGSM UNITS WARRANTED FOR ONE YEAR PARTS.

Standard Export Warranty

- Hatco warrants the products that it manufactures to be free from defects in materials and workmanship, under normal use and service, for a period of one (1) year from the date of purchase when installed and maintained in accordance with Hatco's written instructions, or 18 months from the date of shipment from Hatco.
- Such warranties do not cover: coated incandescent light bulbs, glass components or product failure caused by liming or sediment buildup in tanks, product misuse, tampering or misapplication, improper installation, application of improper voltage, or recalibration of thermostats or high limit switches.
- Labor is not included.
- Customer pays freight and/or delivery from Hatco facilities.

