

6210B-C 6210AB-C

SOFT SERVE FREEZER

1 Flavor, Countertop, Pasteurization A: Pump Feed Model









Most Compact & Versatile single flavor counter model with Auto-Pasteurization with intelligent control

Auto-Pasteurization

Significantly reduces frequency of cleaning to every 21 days with scheduled daily auto-pasteurization

Digital Control and Display

Microprocessor control provides access to system settings and additional functions. Digital interface displays critial info as system status, temperatures, dispense count, errors, etc.

Operation Logging

Logs every operation and error to provide history and data for easy troubleshooting

Auto Programming

Allows automatic switching of operation modes based on preset scheduels

Ideal for any restaurants, convenience stores, dessert stands and delis to serve ice cream and gelato but with desire for significant reduction in labor cost of cleaning.

Hopper Agitator

Maintain product consistency and prevent product separation

Defrost for Cleaning

Increases efficiency during cleaning by heating frozen product in cylinder

Direct Drive Transmission

Eliminates consumable moving parts and increases transmission efficiency

Safety Protections

- Low temperature and motor overload shutoffs to protect in the event of cylinder freeze up
- · High pressure switch to prevent compressor overheating

Refresh and Revive

Restore perfect consistency automatically to reduce product waste and labor cost while ensuring food safety

Self Closing Valve with Speed Control

Automatically prevents product overflow after dispense; Provides flexibility in dispense rate control









6210B-C/6210AB-C

SOFT SERVE FREEZER





SPECIFICATIONS

Flavors	1
Freezing Cylinders	1 x 1.2 L / 1.3 q t
Mix Hoppers	1 x 8 L (5 L for A)
Output Capacity (80 grams)	200 serves/hr
Clearance Requirements	152mm/6" on back

Weight	Kg/lb	Kg/lb (Pump)
Net	113 / 249	118 / 260
Shipping	124 / 273	129 / 284
Volume	0.35 CBM /	12.38 CBF

Dimensions	Net (mm/in)	Shipping (mm/in)
Width	384 / 15.1	450 / 17.7
Depth	674 / 26.5	820 / 32.3
Height	726 / 28.6	950 / 37.4

Electrical	Power (kW)	Total Amps (A)	Fuse (A)
220-240/50/1	1.8	8	16
208-230/60/1	2.0	10	15

 $[\]boldsymbol{\cdot}$ Above specifications are subject to change without notice

FEATURES	
Control System	Sinqle, Digital
Refrigerated Hopper	
Hopper Agitator	\checkmark
Temperature Display	
Standby Mode	\checkmark
Auto Closing Dispensing Valve	
Dispensing Speed Control	\checkmark
Low Mix Indicator Light	
Low Mix Indicator Alarm	\checkmark
Low Temperature Protection	
High Pressure Protection	\checkmark
Defrost & Refresh	
Soft Start	~
Direct Drive Pump	

AVAILABLE OPTIONS	
Water Cooled	\checkmark
Top Air Discharge Chute	



Auto-Pasteurization