

# 6234B-C 6234AB-C

## **SOFT SERVE FREEZER**

2 Flavor, Countertop, Pasteurization A: Pump Feed Model









# Most Compact & Versatile two-flavor table model with Auto-Pasteurization and intelligent controls

#### **Auto-Pasteurization**

Significantly reduces frequency of cleaning to every 21 days with scheduled daily auto-pasteurization

#### **Digital Control and Display**

Microprocessor control provides access to system settings and additional functions. Digital interface displays critial info as system status, temperatures, dispense count, errors, etc.

#### **Operation Logging**

Logs every operation and error to provide history and data for easy troubleshooting

#### **Auto Programming**

Allows automatic switching of operation modes based on preset scheduels

Ideal for any restaurants, convenience stores, dessert stands and delis to serve ice cream and gelato. Small foot print and low energy consumption help reduce operating cost.

#### **Hopper Agitators**

Maintain product consistency and prevent product separation

#### **Defrost for Cleaning**

Increases efficiency during cleaning by heating frozen product in cylinder

#### **Direct Drive Transmission**

Eliminates consumable moving parts, significantly reduces noise and increases transmission efficiency

#### **Safety Protections**

- Low temperature and motor overload shutoffs to protect in the event of cylinder freeze up
- High pressure switch to prevent compressor overheating

#### **Refresh and Revive**

Restore perfect consistency automatically to reduce product waste and labor cost while ensuring food safety

#### **Self Closing Valve with Speed Control**

Automatically prevents product overflow after dispense; Provides flexibility in dispense rate control









# 6234B-C/6234AB-C

## **SOFT SERVE FREEZER**





#### **SPECIFICATIONS**

Flavors	2 + Twist
Freezing Cylinders	2 x 1.2L / 1.3qt
Mix Hoppers	2 x 8.0L (5L for A)
Output Capacity (80 grams)	280 serves/hr
Clearance Requirements	152mm/6" on back

Weight	Kg/lb (Gravity)	Kg/lb (Pump)
Net	135 / 298	145 / 320
Shipping	150 / 331	160/353
Volume	0.48 CBM / 16.78 CBF	

Dimensions	Net (mm/in)	Shipping (mm/in)
Width	444 / 17.5	530 / 20.9
Depth	705 / 27.8	830 / 32.7
Height	880 / 34.6	1080 / 42.5

Electrical	Power (kW)	Total Amps (A)	Fuse (A)
220-240/50/1	2.8	14	20
208-230/60/1	3.0	15	30

 $\boldsymbol{\cdot}$  Above specifications are subject to change without notice

FEATURES	
Control Systems	Double, Digital
Refrigerated Hoppers	
Hopper Agitators	$\checkmark$
Temperature Display	
Standby Mode	$\checkmark$
Auto Closing Dispensing Valves	
Dispensing Speed Control	ightharpoons
Low Mix Indicator Light & Alarm	
Low Temperature Protection	lacksquare
Motor Overload Protection	
High Pressure Protection	lacksquare
Defrost & Refresh	
Soft Start	
Direct Drive Pumps	
Auto-Pasteurization	$\checkmark$

### AVAILABLE OPTIONS

Top Air Discharge Chute



