-60°C LOW TEMP. FREEZERS

PRODUCT

The VT low temperature freezers provides the possibility to maintain temperatures as low as-60°C. Supreme stability, reliability, user-friendliness and ease of cleaning makes the VT LT freezers an ideal solution for laboratories and hospitals.

Nature R refrigerant, cyclopentane insulation combined with recyclable materials, ensures that the freezers are extremely eco-friendly.

SPECIFICATIONS

Gross volume, litres (cu. ft.)	140 (4.9)
Internal storage capacity, litres (cu. ft.)	133 (4.7)
Temperature range (16°C-30°C AMB)	-30°C to -60°C
Temperature probes	1
Compressor	Embraco
Refrigerant	Nature R
Noise level, dB	55
Power consumption, kWh / 24h	3,5
Power consumption, kWh / year	1.278
Voltage, V	220-240
Frequency, Hz	50



FEATURES

Castors	YES
No. of baskets	1
Defrost	Manual
Battery Backup	NO
USB	NO
Alarm connection	NO/NC
Digital controller	XR30CX
Data logging, # logs	NO
Analogue chart recorder	NO
Max no. of standard vials, pcs.	6.804

DIMENSIONS

Height, mm (inches)	850 (33.5)
Height w. castors, mm (inches)	890 (35.1)
Width, mm (inches)	720 (28.3)
Depth, mm (inches)	695 (27.4)
Gross weight, kg (lbs)	59 (130)
Net weight, kg (lbs)	55 (121)

LOADING QUANTITIES

Oty. per 20' / 40' container	46 / 92
Oty. per truck (EU standard)	114





DETAILS

VT 147

-60°C LOW TEMP. FREEZERS

- State-of-the-art unit designed and manufactured by A/S Vestfrost in Denmark
- · Unit optimized for optimal footprint

ENVIRONMENT

- · Eco-friendly, HCFC-free Nature R refrigerant
- · Efficient cyclopentane insulation
- · Low energy consumption

FEATURES

- · Digital XR30CX controller with display
- · Prepared for external logging equipment
- · PT1000 internal temperature measuring probe
- · Top-quality castors for explicit movability
- · Integrated lock to prevent unauthorized access
- · High/low temperature alarm

QUALITY

- · User-friendly and maintenance-free
- · Single compressor system
- · Suitable for rack systems
- · ISO 9001, 14001 & 18001 OHSAS Certified













A/S Vestfrost
Falkevej 12
DK-6705 Esbjerg Ø
www.vestfrostsolutions.com


DIMENSIONS

VT 147

-60°C LOW TEMP. FREEZER







All measurements in mm

DIMENSIONS

Height, mm (inches)	850 (33,46)
Height w. castors, mm (inches)	890 (35,04)
Width, mm (inches)	720 (28,35)
Depth, mm (inches)	600 (600)
Gross weight, kg (lbs)	59 (130)



DIMENSIONS

VT 147

-60°C LOW TEMP. FREEZER



403 (med belegning / with coating 402) 28 53 5 x 53 386

INTERNAL DIMENSIONS

635 (25)
560 (22,05)
440 (17,32)
80
PUR
Coated steel
70
<5

LOADING CAPACITY

Max loading, kg (lbs)	106 (233)
Max no. of standard vials, pcs.	6.804
Max loading in baskets, kg (lbs)	42 (93)

UNIT FEATURES

Porthole for external probe, mm Ø	12
Castors (with brakes)	4 (0)
Inner lids	0
Lid vacuum release	N/A

BASKET FEATURES

Basket material	Coated steel
Basket type	Medium
Quantity	1
Maximum basket load, kg (lbs)	14,50 (31,96)
Weight, kg (lbs)	0,390 (0,86)





STORAGE CAPACITY: RACKS FOR 50 MM BOXES

VF Product no.	No. of boxes	No. of racks	Total no. of boxes
VF311200	6	3	18
VF311220	11	6	66
Total, ex dividers			84



VT 147

STORAGE CAPACITY: RACKS FOR 50 MM BOXES (INCL. DIVIDERS)

VF Product no.	No. of boxes	No. of racks	Total no. of boxes
VF312200	6	3	18
VF312220	11	6	66
Total, vials			6.804



STORAGE CAPACITY: RACKS FOR 75 MM BOXES

VF Product no.	No. of boxes	No. of racks	Total no. of boxes
VF311300	4	3	12
VF311320	8	6	48
Total, ex dividers			60



STORAGE CAPACITY: RACKS FOR 75 MM BOXES (INCL. DIVIDERS)

VF Product no.	No. of boxes	No. of racks	Total no. of boxes
VF312300	4	3	12
VF312320	8	6	48
Total, vials			4.860



STORAGE CAPACITY: RACKS FOR 100 MM BOXES

VF Product no.	No. of boxes	No. of racks	Total no. of boxes
VF311400	3	3	9
VF311420	5	6	30
Total, ex dividers			39



STORAGE CAPACITY: RACKS FOR 100 MM BOXES (INCL. DIVIDERS)

Total, vials			3.159
VF312420	5	6	30
VF312400	3	3	9
VF Product no.	No. of boxes	No. of racks	Total no. of boxes





